Cordless Drill Driver / Cordless Impact Drill Driver

A 18 / ASB 18



With a total of 4 magnetic bit holders, two on both sides of the battery holder, the desired bit is always to hand.

In difficult situations the impulse mode delivers a critical boost, e.g. for releasing immovable screws or controlling

the first few turns when drilling into

Product features

• Extreme Power

smooth surfaces.

- Ergo-Balance Principle
- Impulse function
- Brushless motor
- Pressure-sensitive trigger

Application area

- Drilling
- Driving
- Percussion drilling (ASB 18I)
- Ideal for construction sites

Product description

To overcome the toughest challenges, we have given the new-generation A 18 and ASB 18 an especially rugged specification and extra power.

Its impact drill function makes the ASB 18 a genuine all-rounder.

The upgraded PowerTanks for our cordless tools feature advanced processor-controlled battery technology. A key advantage lies in continuous monitoring of all the relevant parameters of the individual battery cells, including temperature and charge.

Technical data	A 18	ASB 18	
Clamping collar diameter	43 mm	43 mm	
Chuck opening	13 mm	13 mm	
Max. drilling diameter in wood / steel	68 / 13 mm	50 / 13 mm	
Torque soft / hard	65 / 130 Nm	65 / 130 Nm	
Impulse torque (soft)	65 Nm	65 Nm	
Nominal no-load speed 1st setting	0 - 560 1/min	0 - 560 1/min	
Nominal no-load speed 2nd setting	0 - 1.960 1/min	0 - 1.960 1/min	
Weight (including battery)	1.8 kg	1.8 kg	
Voltage rating	18 V	18 V	
Impact rate		38.000 1/min	
Torque settings	11	11	
Vibration (measured in metal/reinforced cond	,	< 2.5 m/s / 15.5 m/s	
Noise level dB(A)	72 dB(A)	92 dB(A)	
Sound power level (LwA)	88 dB(A)	103 dB(A)	

Delivery specification

Cordless Drill Driver A 18 - PURE in the T-MAX	91C802
Cordless Drill Driver A 18 in the T-MAX	91C801
Cordless Impact Drill Driver ASB 18 - PURE in the T-MAX	91C902
Cordless Impact Drill Driver ASB 18 in the T-MAX	91C901

Delivery scope includes	PURE	T-MAX
1 Quick-release chuck A-SBF 13	x	х
1 Quick-release bit holder A-SBH	x	х
1 Belt clip	x	x
1 Auxiliary handle	x	x
1 Battery PowerTank 18 M 72 LiHD		x
1 Battery PowerTank 18 M 99 LiHD		x
1 Battery PowerStation APS M		х

PG A Price list page 16











Two spirit levels clearly indicate the 90° angle when driving screws and drilling – horizontally and vertically.



With more power than before, the 18 V machines make light work of drilling even 68 mm holes in wood.



The electronic anti-kickback function provides extra safety by actively shutting down the motor and protecting the wrist against sudden twisting.



Powerful impact drill functionality delivers excellent results when drilling holes in masonry.

	Ac	cessor	ies / Tools		
Image	Description	Ref. No.	Image	Description	Ref. No
	Quick-release	206772		Ø 12 mm	090253
	chuck A-SBF 13			Ø 14 mm	090254
	13 mm			Ø 16 mm	090255
				Ø 18 mm	090256
				Ø 20 mm	090257
	Quick release bit helder A	206766		Ø 22 mm	090258
	Quick-release bit holder A-	200700		Ø 24 mm	090259
	SBH			Ø 26 mm	090260
				Ø 28 mm	090261
				Ø 30 mm	090262
	Angle head A-WV 18	094459		Ø 30 IIIII	090202
2	up to 100 Nm	094439		Lewis auger bit with	
	up to 100 Mili			hexagonal shank total length	
10				650 mm	
				Ø 10 mm	090240
~	Torque head A-DMV x3	094450		Ø 12 mm	090241
	3:1 ratio			Ø 14 mm	090242
6				Ø 16 mm	090243
				Ø 18 mm	090244
4	Battery PowerTank			Ø 20 mm	090245
	Dattery Fower talk			Ø 22 mm	090246
	8 M 72 LiHD (18 V, 72 Wh, 4,0 Ah)	094500		Ø 24 mm	090247
CAS	18 M 99 LiHD (18 V, 99 Wh, 5,5 Ah)	094503		Ø 26 mm	090248
	18 M 144 LiHD (18 V, 144 Wh, 8 Ah	094498		Ø 28 mm	090249
-	Battery PowerStation APS M	094492		Ø 30 mm	090248
	18 V	094492			
				Case with auger bits 650	093292
	Battery PowerStation APS M+	094509	- 5 M 3 M	5 pieces Lewis auger bits	
	High-speed charger, 18 V		48 25 7	Ø 12, 14, 16, 18, 20 mm	
TE SE	Lewis auger bit with			Case with auger bits 460	093291
	hexagonal shank total length			6 pieces Lewis auger bits	
	320 mm			Ø 8, 10, 12, 14, 16, 18 mm	
	Ø 6 mm	090279			
	Ø 7 mm	090280		Case with auger bits 320	093290
	Ø 8 mm	090263		6 pieces Lewis auger bits	
	Ø 9 mm	090264		Ø 8, 10, 12, 14, 16, 18 mm	
	Ø 10 mm	090265		2 0, 10, 12, 11, 10, 10 11111	
	Ø 12 mm	090266			
	Ø 14 mm	090267		Drilling station	
	Ø 16 mm	090268		BST 320	961210
	Ø 18 mm	090269	•	201 020	301210
	Ø 20 mm	090270		BST 460	961211
	Ø 22 mm	090271	1	201.100	331211
	Ø 24 mm	090272		BST 460 S	961215
	Ø 26 mm	090273		231 400 0	001210
	Ø 28 mm	090274	1000	BST 650 S	
	Ø 30 mm	090275		50, 000 0	961216
-V-0-0-	Lewis auger bit with hexagonal shank total length 460 mm				

090251

090252

Ø8mm

Ø 10 mm

All auger bits shown here are guaranteed against breakage of the lead screw. Subject to the general guarantee conditions.